

STRONGVIEW & STRONGVIEW L

MOTORIZED SCREEN

Standard Format: 13'-1" (4m) to 17'-11" (5.46m) image width
Large Format: 18' (5.5m) to 25' (7.62m) image width

The sleek and practical **STRONGVIEW & STRONGVIEW L** electric screen systems are used for projects needing a smaller motorized projection screen system than our StrongviewXL. The tubular motor runs quietly and is dependable even with heavy usage. Side tension tabs ensure the screen surface is perfectly tensioned for flawless projection. The Strongview series can be used with any of our non-coated rear view and front view screens.



FEATURES

- ▶ UL/cUL approved, 1/2 HP tubular motor, 120V - 5amp
- ▶ Separate control box with wireless module
- ▶ Truss dimensions :
Standard format
Height : 14" Depth : 10-3/4"
(35.5cm x 27.3cm)
- ▶ **Large format**
Height : 15 1/2" Depth : 13 1/2"
(39.37cm x 34.29cm)
- ▶ Head truss protected by 3mm matte black expanded PVC cover panels
- ▶ Rigid 1" x 1" (25.4mm x 25.4mm) steel tubing head truss assembly
- ▶ Nylon side tension tab cable
- ▶ Custom, welded black PVC masking borders
- ▶ Handheld RF wireless remote control included (2)
- ▶ Low voltage control trigger (Down/Stop/Up) on terminal strip
- ▶ 1 x 120V male 'U'-ground connector

OPTIONS

- ▶ 1/8" (3.2 mm) thick mat black aluminum composite panel with polyethylene core (add 1/8" (3.2mm) to truss height and 1/4" (6.35mm) to truss depth)
- ▶ 220V – 240V operation
- ▶ Wired wall mount key pad remote control (VMR4)
- ▶ CUL/CSA twist lock male connector (to be specified)
- ▶ Adaptable rigging hardware (to be specified)
- ▶ Perforated, non-perforated front or rear projection surfaces (non-coated)
- ▶ Independent masking system upgrade